



208V

240V

240V

480V

PHASE 1

ELS 200 S

ROHDE ERGO-LOAD-SYSTEM CHAMBER KILN



PHASE 1

208V

240V

240V

480V

ELS 200 S

ROHDE ERGO-LOAD-SYSTEM CHAMBER KILN

Volume	7.1 cft
Int Dimensions	18" x 24" x 27"
Performance	13.2 kW
Tapp*	2354 °F/ Cone 10

*Application temperature for long-term and continuous use

OVERVIEW

Product Group	Kiln
Design	Chamber Kiln
Type	Ergonomic Loading System
Cone	10

ENERGY

Energy Type	Electrical
Performance	13.2 kW
Amps	36.6 A
Voltage	208 V
Plug	NEMA 15-50
Electrics	Kiln back wall
Phase	3

DIMENSIONS

Volume	7.1 cft
Int Dimensions	18" x 24" x 27"
Ext Dimensions	31" x 49" x 66"
Weight	1,213 lb

EQUIPMENT

Insulation	Triple-layer insulation system
Heating	5-side heating
Heating Elements	Mounted on support rods
Controller	TR 511
Peepholes	1
Zone Control	1 zone
Inlet Air	Manual
Exhaust Air	Auto
Thermocouple	Type S
Kiln Floor	Manually operated
Ceiling	R-SiC ceiling support prevents cracks and falling particles



PHASE 1

208V

240V

240V

480V

ELS 200 S

ROHDE ERGO-LOAD-SYSTEM CHAMBER KILN

Volume	7.1 cft
Int Dimensions	18" x 24" x 27"
Performance	13.2 kW
Tapp*	2354 °F/ Cone 10

*Application temperature for long-term and continuous use

OVERVIEW

Product Group	Kiln
Design	Chamber Kiln
Type	Ergonomic Loading System
Cone	10

ENERGY

Energy Type	Electrical
Performance	13.2 kW
Amps	31.7 A
Voltage	240 V
Plug	NEMA 15-50
Electrics	Kiln back wall
Phase	3

DIMENSIONS

Volume	7.1 cft
Int Dimensions	18" x 24" x 27"
Ext Dimensions	31" x 49" x 66"
Weight	1,213 lb

EQUIPMENT

Insulation	Triple-layer insulation system
Heating	5-side heating
Heating Elements	Mounted on support rods
Controller	TR 511
Peepholes	1
Zone Control	1 zone
Inlet Air	Manual
Exhaust Air	Auto
Thermocouple	Type S
Kiln Floor	Manually operated
Ceiling	R-SiC ceiling support prevents cracks and falling particles



PHASE 1

208V

240V

240V

480V

ELS 200 S

ROHDE ERGO-LOAD-SYSTEM CHAMBER KILN

Volume	7.1 cft
Int Dimensions	18" x 24" x 27"
Performance	13.2 kW
Tapp*	2354 °F/ Cone 10

*Application temperature for long-term and continuous use

OVERVIEW

Product Group	Kiln
Design	Chamber Kiln
Type	Ergonomic Loading System
Cone	10

ENERGY

Energy Type	Electrical
Performance	13.2 kW
Amps	55.0 A
Voltage	240 V
Plug	Direct wire
Electrics	Kiln back wall
Phase	1

DIMENSIONS

Volume	7.1 cft
Int Dimensions	18" x 24" x 27"
Ext Dimensions	31" x 49" x 66"
Weight	1,213 lb

EQUIPMENT

Insulation	Triple-layer insulation system
Heating	5-side heating
Heating Elements	Mounted on support rods
Controller	TR 511
Peepholes	1
Zone Control	1 zone
Inlet Air	Manual
Exhaust Air	Auto
Thermocouple	Type S
Kiln Floor	Manually operated
Ceiling	R-SiC ceiling support prevents cracks and falling particles



PHASE 1

208V

240V

240V

480V

ELS 200 S

ROHDE ERGO-LOAD-SYSTEM CHAMBER KILN

Volume	7.1 cft
Int Dimensions	18" x 24" x 27"
Performance	13.2 kW
Tapp*	2354 °F/ Cone 10

*Application temperature for long-term and continuous use

OVERVIEW

Product Group	Kiln
Design	Chamber Kiln
Type	Ergonomic Loading System
Cone	10

ENERGY

Energy Type	Electrical
Performance	13.2 kW
Amps	15.9 A
Voltage	480 V
Plug	L16-20P
Electrics	Kiln back wall
Phase	3

DIMENSIONS

Volume	7.1 cft
Int Dimensions	18" x 24" x 27"
Ext Dimensions	31" x 49" x 66"
Weight	1,213 lb

EQUIPMENT

Insulation	Triple-layer insulation system
Heating	5-side heating
Heating Elements	Mounted on support rods
Controller	TR 511
Peepholes	1
Zone Control	1 zone
Inlet Air	Manual
Exhaust Air	Auto
Thermocouple	Type S
Kiln Floor	Manually operated
Ceiling	R-SiC ceiling support prevents cracks and falling particles