



208V

240V

480V

ELS 600 S

ROHDE ERGO-LOAD-SYSTEM CHAMBER KILN



208V

240V

480V

ELS 600 S

ROHDE ERGO-LOAD-SYSTEM CHAMBER KILN

Volume	21.2 cft
Int Dimensions	28" x 33" x 40"
Performance	40 kW
Tapp*	2354 °F/ Cone 10

*Application temperature for long-term and continuous use

OVERVIEW

Product Group	Kiln
Design	Chamber Kiln
Type	Ergonomic Loading System
Cone	10

ENERGY

Energy Type	Electrical
Performance	40 kW
Amps	110.9 A
Voltage	208 V
Plug	Direct wire
Electrics	Control cabinet
Phase	3

DIMENSIONS

Volume	21.2 cft
Int Dimensions	28" x 33" x 40"
Ext Dimensions	59" x 59" x 83"
Weight	2,425 lb

EQUIPMENT

Insulation	Triple-layer insulation system
Heating	5-side heating
Heating Elements	Mounted on support rods
Controller	TR 532
Peepholes	3
Zone Control	3 zone
Inlet Air	Auto
Exhaust Air	Auto
Thermocouple	Type S
Kiln Floor	Manually operated
Ceiling	R-SiC ceiling support prevents cracks and falling particles



208V

240V

480V

ELS 600 S

ROHDE ERGO-LOAD-SYSTEM CHAMBER KILN

Volume	21.2 cft
Int Dimensions	28" x 33" x 40"
Performance	40 kW
Tapp*	2354 °F/ Cone 10

*Application temperature for long-term and continuous use

OVERVIEW

Product Group	Kiln
Design	Chamber Kiln
Type	Ergonomic Loading System
Cone	10

ENERGY

Energy Type	Electrical
Performance	40 kW
Amps	96.1 A
Voltage	240 V
Plug	Direct wire
Electrics	Control cabinet
Phase	3

DIMENSIONS

Volume	21.2 cft
Int Dimensions	28" x 33" x 40"
Ext Dimensions	59" x 59" x 83"
Weight	2,425 lb

EQUIPMENT

Insulation	Triple-layer insulation system
Heating	5-side heating
Heating Elements	Mounted on support rods
Controller	TR 532
Peepholes	3
Zone Control	3 zone
Inlet Air	Auto
Exhaust Air	Auto
Thermocouple	Type S
Kiln Floor	Manually operated
Ceiling	R-SiC ceiling support prevents cracks and falling particles



208V

240V

480V

ELS 600 S

ROHDE ERGO-LOAD-SYSTEM CHAMBER KILN

Volume	21.2 cft
Int Dimensions	28" x 33" x 40"
Performance	40 kW
Tapp*	2354 °F/ Cone 10

*Application temperature for long-term and continuous use

OVERVIEW

Product Group	Kiln
Design	Chamber Kiln
Type	Ergonomic Loading System
Cone	10

ENERGY

Energy Type	Electrical
Performance	40 kW
Amps	48.2 A
Voltage	480 V
Plug	Direct wire
Electrics	Control cabinet
Phase	3

DIMENSIONS

Volume	21.2 cft
Int Dimensions	28" x 33" x 40"
Ext Dimensions	59" x 59" x 83"
Weight	2,425 lb

EQUIPMENT

Insulation	Triple-layer insulation system
Heating	5-side heating
Heating Elements	Mounted on support rods
Controller	TR 532
Peepholes	3
Zone Control	3 zone
Inlet Air	Auto
Exhaust Air	Auto
Thermocouple	Type S
Kiln Floor	Manually operated
Ceiling	R-SiC ceiling support prevents cracks and falling particles