



208V

240V

ECOTOP 250 S

ROHDE TOPLOADER



208V

240V

ECOTOP 250 S

ROHDE TOPLOADER

Volume	8.8 cft
Int Dimensions	28.6" x 24.4" x 26.9"
Performance	11.8 kW
Tapp*	2354 °F/Cone 10

*Application temperature for long-term and continuous use

OVERVIEW

Product Group	Kiln
Design	Toploader
Type	Ecotop Series
Cone	10
Installation	Main body can be separated into two sections for easier assembly

DIMENSIONS

Volume	8.8 cft
Int Dimensions	28.6" x 24.4" x 26.9"
Ext Dimensions	47.1" x 37.1" x 39.4"
Weight	426 lb

ENERGY

Energy Type	Electrical
Performance	11.8 kW
Amps	32.8 A
Voltage	208 V
Plug	NEMA 15-50
Phase	3

EQUIPMENT

Insulation	2-layer with 3" firebrick and 1.38" microporous insulation
Heating	All-around
Heating Elements	Recessed into bricks
Controller	TR 511
Peepholes	1
Thermocouple	Type S



208V240V

ECOTOP 250 S

ROHDE TOPLOADER

Volume	8.8 cft
Int Dimensions	28.6" x 24.4" x 26.9"
Performance	11.8 kW
Tapp*	2354 °F/Cone 10

*Application temperature for long-term and continuous use

OVERVIEW	
Product Group	Kiln
Design	Toploader
Type	Ecotop Series
Cone	10
Installation	Main body can be separated into two sections for easier assembly

DIMENSIONS	
Volume	8.8 cft
Int Dimensions	28.6" x 24.4" x 26.9"
Ext Dimensions	47.1" x 37.1" x 39.4"
Weight	426 lb

ENERGY	
Energy Type	Electrical
Performance	11.8 kW
Amps	28.4 A
Voltage	240 V
Plug	NEMA 15-50
Phase	3

EQUIPMENT	
Insulation	2-layer with 3" firebrick and 1.38" microporous insulation
Heating	All-around
Heating Elements	Recessed into bricks
Controller	TR 511
Peepholes	1
Thermocouple	Type S