



208V

240V

ECOTOP 300 S

ROHDE TOPLOADER



208V240V

ECOTOP 300 S

ROHDE TOPLOADER

Volume	10.6 cft
Int Dimensions	33.1" x 24.4" x 26.9"
Performance	13.3 kW
Tapp*	2354 °F/Cone 10

*Application temperature for long-term and continuous use

OVERVIEW	
Product Group	Kiln
Design	Toploader
Type	Ecotop Series
Cone	10
Installation	Main body can be separated into two sections for easier assembly

DIMENSIONS	
Volume	10.6 cft
Int Dimensions	33.1" x 24.4" x 26.9"
Ext Dimensions	51.6" x 36.5" x 39.4"
Weight	460 lb

ENERGY	
Energy Type	Electrical
Performance	13.3 kW
Amps	37.0 A
Voltage	208 V
Plug	NEMA 15-50
Phase	3

EQUIPMENT	
Insulation	2-layer with 3" firebrick and 1.38" microporous insulation
Heating	All-around
Heating Elements	Recessed into bricks
Controller	TR 511
Peepholes	1
Thermocouple	Type S



208V

240V

ECOTOP 300 S

ROHDE TOPLOADER

Volume	10.6 cft
Int Dimensions	33.1" x 24.4" x 26.9"
Performance	13.3 kW
Tapp*	2354 °F/Cone 10

*Application temperature for long-term and continuous use

OVERVIEW

Product Group	Kiln
Design	Toploader
Type	Ecotop Series
Cone	10
Installation	Main body can be separated into two sections for easier assembly

DIMENSIONS

Volume	10.6 cft
Int Dimensions	33.1" x 24.4" x 26.9"
Ext Dimensions	51.6" x 36.5" x 39.4"
Weight	460 lb

ENERGY

Energy Type	Electrical
Performance	13.3 kW
Amps	32.0 A
Voltage	240 V
Plug	NEMA 15-50
Phase	3

EQUIPMENT

Insulation	2-layer with 3" firebrick and 1.38" microporous insulation
Heating	All-around
Heating Elements	Recessed into bricks
Controller	TR 511
Peepholes	1
Thermocouple	Type S