



208V

240V

ECOTOP 60

ROHDE TOPLOADER



208V

240V

ECOTOP 60

ROHDE TOPLOADER

Volume	2.1 cft
Int Dimensions (Ø x h)	15.7" x 18"
Performance	3.3 kW
Tapp*	2300 °F/Cone 9

*Application temperature for long-term and continuous use

OVERVIEW

Product Group	Kiln
Design	Toploader
Type	Ecotop Series
Cone	9

DIMENSIONS

Volume	2.1 cft
Int Dimensions	15.7" x 18"
Ext Dimensions	34.9" x 29.5" x 30.6"
Weight	197 lb

ENERGY

Energy Type	Electrical
Performance	3.3 kW
Amps	15.9 A
Voltage	208 V
Plug	NEMA 6-20
Phase	1

EQUIPMENT

Insulation	2-layer with 3" firebrick and 1.38" microporous insulation
Heating	All-around
Heating Elements	Recessed into bricks
Controller	TR 511
Peepholes	1
Thermocouple	Type S



208V

240V

ECOTOP 60

ROHDE TOPLOADER

Volume	2.1 cft
Int Dimensions (Ø x h)	15.7" x 18"
Performance	3.6 kW
Tapp*	2300 °F/Cone 9

*Application temperature for long-term and continuous use

OVERVIEW

Product Group	Kiln
Design	Toploader
Type	Ecotop Series
Cone	9

DIMENSIONS

Volume	2.1 cft
Int Dimensions	15.7" x 18"
Ext Dimensions	34.9" x 29.5" x 30.6"
Weight	197 lb

ENERGY

Energy Type	Electrical
Performance	3.6 kW
Amps	15.0 A
Voltage	240 V
Plug	NEMA 6-20
Phase	1

EQUIPMENT

Insulation	2-layer with 3" firebrick and 1.38" microporous insulation
Heating	All-around
Heating Elements	Recessed into bricks
Controller	TR 511
Peepholes	1
Thermocouple	Type S