



208V

240V

ECOTOP 95 S

ROHDE TOPLOADER



208V

240V

ECOTOP 95 S

ROHDE TOPLOADER

Volume	3.4 cft
Int Dimensions (Ø x h)	20.5" x 18"
Performance	7.3 kW
Tapp*	2354 °F/Cone 10

*Application temperature for long-term and continuous use

OVERVIEW

Product Group	Kiln
Design	Toploader
Type	Ecotop Series
Cone	10

DIMENSIONS

Volume	3.4 cft
Int Dimensions	20.5" x 18"
Ext Dimensions	40.3" x 32.8" x 30.4"
Weight	245 lb

ENERGY

Energy Type	Electrical
Performance	7.3 kW
Amps	35.1 A
Voltage	208 V
Plug	NEMA 6-50
Phase	1

EQUIPMENT

Insulation	2-layer with 3" firebrick and 1.38" microporous insulation
Heating	All-around
Heating Elements	Recessed into bricks
Controller	TR 511
Peepholes	1
Thermocouple	Type S



208V

240V

ECOTOP 95 S

ROHDE TOPLOADER

Volume	3.4 cft
Int Dimensions (Ø x h)	20.5" x 18"
Performance	7.3 kW
Tapp*	2354 °F/Cone 10

*Application temperature for long-term and continuous use

OVERVIEW

Product Group	Kiln
Design	Toploader
Type	Ecotop Series
Cone	10

DIMENSIONS

Volume	3.4 cft
Int Dimensions	20.5" x 18"
Ext Dimensions	40.3" x 32.8" x 30.4"
Weight	245 lb

ENERGY

Energy Type	Electrical
Performance	7.3 kW
Amps	30.4 A
Voltage	240 V
Plug	NEMA 6-50
Phase	1

EQUIPMENT

Insulation	2-layer with 3" firebrick and 1.38" microporous insulation
Heating	All-around
Heating Elements	Recessed into bricks
Controller	TR 511
Peepholes	1
Thermocouple	Type S